



TECHNICAL DATA SHEET

ENVIRO-SAFE INJECTION FLUID

DESCRIPTION

Construction Chemicals have developed this solvent based Chemical DPC injection fluid specifically to eliminate the problems usually associated with solvent systems.

Enviro-Safe Injection Fluid is produced using an ultra low odour, high flashpoint solvent, which, when combined with the tried and tested Polyoxoaluminium Stearate, produces a Non-flammable fluid which has virtually no smell. This diminishes the safety considerations usually associated with DPC injection, viz. suspension of work by other trades in the treatment areas is not necessary.

As with other injection products, **Enviro-Safe** is manufactured to the requirement of BS.EN. ISO9002. The use of the fluid follows the same procedures and guidelines as POAS Injection Fluid.

METHOD of USE.

Enviro-Safe Injection Fluid is applied under pressure to either brickwork or random stone walls.

Enviro-Safe should be applied at the following rate for typical brickwork.

- 1) 115mm (4½+) Wall :: 3.3 linear metres / 5 litres.
- 2) 230mm (9+) Wall :: 1.68 linear metres / 5 litres.

Note: - Refer to the Construction Chemicals DPC Injection Manual for detail of application.

HEALTH and SAFETY.

Enviro-Safe Injection Fluid contains solvent and should be used only in well ventilated areas. The product is not classed as hazardous in normal use.

If swallowed, do not induce vomiting because of the aspiration hazard. Seek Medical Attention and show product detail (label) or Safety Data Sheet.