

TECHNICAL DATA SHEET

CONSTRUCTION CHEMICALS FILLET SEAL BARRIER MORTAR

Description

Construction Chemicals Fillet Seal is a hydrophobic, non-shrinking repair mortar. It is an integral part of the Construction Chemicals cellar or below ground Tanking System; Fillet Seal is used to create a waterproof flexible fillet at wall/wall and wall/floor junctures.

Form Supplied: Powder
Pack Sizes: 25 Kg bags
Colour range: Grey
Contains: Cement, polymers, and additives

Properties


Forms a water resistant mortar seal that does not shrink and has excellent adhesion to concrete and mortar. Can be used as a general repair mortar where shrinkage must be avoided. Construction Chemicals Fillet Seal has a long pot life, typically 5 hours ensuring that wastage is kept to a minimum.

Usage

Construction Chemicals Fillet Seal should be applied to a damp substrate. When using with the Construction Chemicals Tanking System, apply a 25 mm fillet into all vertical and horizontal joints. It should be applied onto the first coat of Tanking before it has cured. This will typically be around 1 hour after the application of the Tanking slurry. Care should be taken not to damage the underlying coating. Allow the Fillet Seal to stiffen for 2 – 3 hours and then apply the second coat of Tanking Slurry to the substrate and over The Fillet Seal.



Fillet Seal can also be used as a general repair compound for patch filling of masonry, walls and floors. When cured it has a compressive strength of >40N/mm². Do not use in when temperatures are below 5 degrees C.



INSTALLATION OF FILLET SEAL

- 1 Apply priming coat if specified and first coat of Tanking Slurry.
- 2 Insert 25mm fillet to floor/ wall or wall/ wall joint.
- 3 Apply second coat of Tanking slurry

Coverage

When used as a 25 mm fillet around 1 kg per linear metre will be required. When used as a repair compound 25 kg mixed with water will produce around 15 litres of mortar.

Shelf Life

12 months when stored unopened and above ground in cool dry conditions.

Health and Safety

R36 Irritating to skin.

R41 Risk of serious damage to eyes.

Contact between cement powder and body fluids (e.g. sweat and eye fluids) may cause irritation, dermatitis or burns. There is a risk of serious damage to eyes. Wear suitable protective clothing, gloves and eye/face protection. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. After contact with skin wash immediately with plenty of clean water. Keep out of reach of children.

For full health and safety information see Safety Data Sheet.